

# CHINON

## CM-5

**SEMI-AUTOMATIC SLR WITH FULL MANUAL CONTROL  
AND BAYONET MOUNT LENS**

### FEATURES

- Creative full manual control VIA match LED exposure system.
- Seiko designed metal shutter with speeds from 1 second to 1/1000.
- Instant responding silicon blue cell employed in the center weighted full aperture metering system.
- Built-in self-timer.
- Compact/lightweight design.
- Accepts lenses with universal bayonet mount and accepts thread mount lenses with optional adapter.
- Memo holder so that you always know what type of film is in your camera.
- Accepts CHINON Power Winder for single frame advance.
- Detachable hand grip with spare battery compartment.

### ACCESSORIES

#### PRODUCT NUMBER

#### DESCRIPTION

28940	Wireless remote control for power winders
28900	S-180 auto electronic flash.
28910	S-240 dedicated automatic electronic flash.
28920	S-280 "bounce" dedicated automatic electronic flash.
28925	S-360 "bounce and swivel" dedicated automatic electronic flash with information display by LED.
28350	Right angle finder.
28202	Eyeiece diopter -3.0
28212	Eyeiece diopter +1.0
28222	Eyeiece diopter +3.0

28880	Neck strap for "Series 5" SLR's
28405	Extension tube set (12, 20, 36mm)
28415	Extension bellows
28560	Rubber eyepiece.
28640	Metal table tripod
28000	Info Back digital data imprinting unit.
28060	Info Back-2 digital data imprinting unit with LCD monitor window.
28080	Auto date digital data imprinting unit.
33600	CHINON 35- 70 f/3.3- 4.5 auto focus lens
26210	CHINON 50 AF f/1.7 auto focus lens
24910	Power Winder PW-610
6020	Lens hood (49mm)
28365	Detachable hand grip with spare battery compartment



\* The hand grip is optional

# CHINON

# CHINON

## CM-5

### SPECIFICATIONS

- **Type:** 35mm SLR compact camera with LED type light measuring system.
- **Picture Format:** 24 × 36mm.
- **Lens Mount:** Chinon Universal Bayonet Mount.
- **Mirror:** Large, Quick return, shockless system.
- **Shutter:** Seiko MFC metal focal plane shutter.
- **Shutter Speeds:** 1 sec. – 1/1000 sec., "B".
- **Viewfinder:** Fixed eye-level pentaprism, central split image with microprism collar and ground glass.
- **Viewfinder Magnification:** 0.87 × (@ 50mm, ∞).
- **Viewfinder Visibility:** 92%.
- **Exposure Meter:** TTL, Center weighted full aperture system employing one silicon blue photo cell, 3 steps exposure indicator with 3 LEDs.
- **Exposure Range:** EV +2 (F/1.9, 1 sec.) to EV +18 (F/16, 1/1000 sec.) – ASA100 F/1.9 lens.
- **Meter ON/OFF Switch:** Meter switch is activated when shutter release button is pressed, meter remains on for several seconds after finger is lifted off release button.

- **ASA Range:** 25 – 1600 (DIN 15 – 33) with safety lock.
- **Film Advance:** Single stroke in an arc of 130° with 25° stand off.
- **Film Counter:** Automatically indicates number of exposures and resets to "S" when camera back is opened.
- **Film Rewind:** Folding crank type.
- **Accessory Shoe:** Hot Shoe type with X sync.
- **Self-Timer:** Built-in.
- **Synchronization:** Strobe Sync. at 1/60 sec.
- **Power Winder Contacts:** Power winder electronic contacts are built in for a single frame picture advance.
- **Power Source:** Two 1.5 V Alkaline batteries (LR44, A76) or two 1.5 V silver oxide batteries (SR44, S76, G-13).
- **Battery Test:** Built-in with LED indicator.
- **Accessories:** Multi-coated lenses, Auto electronic flashes, carrying case, and many more.
- **Body Dimensions:** 135.5 (W) × 86.0 (H) × 50.5 (D) mm. (5.33" × 3.38" × 1.99")
- **Body Weight:** 455 grams (16.05 oz).

PRODUCT NUMBER	DESCRIPTION
24878	CM-5 Black body
24888	CM-5 Silver gray body
28365	Hand grip

