

# CHINON

## CP-X PROGRAM

FULLY AUTOMATIC PROGRAM SLR WITH  
AUTOMATIC EXPOSURE, COMPLETE MANUAL EXPOSURE  
AND AUTOMATIC (DX) FILM SPEED SETTING

### FEATURES:

- Program mode for action photography.
- "DX" Electronics automatically set ASA/ISO film speed.
- Creative full manual override via LED "OK" indicator in viewfinder.
- Full information viewfinder employing 7 digital LED's indicating over/under (red) or proper exposure (green), flash ready (red), program AE (green), aperture priority AE (red), and manual exposure mode (red) and slow shutter speed warning (green).
- Electronic metal Seiko shutter with automatic stepless speeds from 1 sec. to 1/1000 sec.
- Detachable hand grip supplies power to camera body.
- Electronic visual 10 second self-timer.
- Instant responding silicon blue cell metering system.
- Accepts "K", "KA" and "RK" mount lenses.
- Dedicated electronic flash circuitry.
- Exposure memory lock for backlight or recomposing situations.

- Accepts optional CHINON power winders, wireless remote control system, dedicated flashes, Infoback and Auto Date Data Backs, super multi-coated lenses, carrying cases and more.

### ACCESSORIES:

PRODUCT NUMBER	DESCRIPTION
28905	S-200 automatic electronic flash.
28940	Wireless remote control for power winders.
28915	S-250 dedicated automatic electronic flash.
28920	S-280 "bounce" dedicated automatic electronic flash.
28922	S-300 dedicated automatic electronic flash with information display by LED.
28925	S-360 "bounce and swivel" dedicated automatic electronic flash with information display by LED.
28935	S-480 "bounce and swivel" dedicated automatic electronic thyristor flash.
28350	Right angle finder
28202	Eyeiece diopter -3.0
28212	Eyeiece diopter +1.0
28222	Eyeiece diopter +3.0
28880	Neck strap for "Series 5" SLR's
27610	Wide Shoulder Strap with "CHINON LOGO"
28405	Extension tube set (12, 20, 36mm)
28415	Extension bellows



APPROXIMATE SIZE



28560	Rubber eyepiece
28640	Metal table tripod
28060	Info Back-2 digital data imprinting unit with LCD monitor window
28080	Auto Date digital data imprinting unit
24905	Power Winder PW-600
24910	Power Winder PW-610

# CHINON

# CHINON

## CP-X PROGRAM

### SPECIFICATIONS

- **Type:** 35 mm automatic compact SLR camera with TTL full aperture programmed AE (instant stop-down re-metering), Aperture priority AE, manual exposure system, and auto film speed setting.
- **Picture Format:** 24 × 36 mm.
- **Lens Mount:** CHINON universal bayonet mount (K, KA, RK mount compatible).
- **Mirror:** Quick return mirror.
- **Shutter:** Electromagnetically controlled focal plane shutter, stepless speeds from 1 sec. to 1/1000 sec. on automatic; maximum operation time at AE (A or P mode) is 8 seconds, 11 speeds from 1 to 1/1000 sec. on manual exposure. Electronically controlled automatic and manual exposure.
- **Shutter Release:** Electromagnetic type shutter release with safety lock and provision for cable release.
- **Viewfinder:** Fixed eyelevel pentaprism central split image with micro prism collar, 7 LED's indicate over/under and proper exposure, flash ready, program AE, aperture priority AE, and manual exposure mode. Slow shutter speed warning by blinking "OK" LED in viewfinder when the shutter speed is slower than 1/30 sec.
- **Viewfinder magnification:** 0.87X (@50 mm, at infinity)
- **Viewfinder visibility:** 92%
- **Exposure Meter:** TTL center weighted full aperture system employing silicon blue cell.
- **Exposure Range:** EV+1 (F1.4, 1 sec.) to EV+19 (F22, 1/1000 sec.) a ISO 100, F1.4/50 mm lens.

- **AE Lock:** Built-in exposure memory lock system.
- **ISO Range:** 25-5000 for DX-coded film with 1/3EV segment. 25-3200 for non-DX film with 1/3EV segment.
- **Film Advance:** Single stroke in an arc off 130° with 25° stand off. Motorized film advance with optional power winder.
- **Film Loading:** Multi-slot take-up spool type.
- **Film Rewind:** By depressing the rewind button and cranking the rewind lever.
- **Film Counter:** Automatically indicates number of exposure and resets to "S" when the camera back is opened.
- **Selftimer:** Electronically controlled at 10 sec. with flashing red LED.
- **Accessory Shoe:** Hot Shoe type with "X" sync and a contact for CHINON dedicated flash.
- **"X" Synchronization:** "X" flash sync at 1/100 sec. with dedicated flash (1/60 sec. with non-dedicated flash).
- **Slow Synchronization:** 1/60 sec. or slower at manual.
- **Power Source:** Four 1.5 alkaline (LR44) or silver oxide (SR44, G13) batteries, or two 3 V lithium batteries (CR-1/3N).
- **Power Hold System:** 12 sec. in manual exposure mode.
- **Battery Check:** Built-in with LED indicator.
- **Accessories:** CHINON power winders, Dedicated flashes, Info Back-2 data imprinting unit, Auto Date data imprinting unit, Super multi-coated lenses, Deluxe carrying cases and many more.
- **Dimensions:** 136(W) × 88(H) × 51(D) mm (5.35" × 3.46" × 2.01")
- **Weight:** 498 g (17.57 oz)

PRODUCT NUMBER	DESCRIPTION
25010	CP-X body

