

CHINON 35EE II

DISC



SPECIFICATIONS FOR CHINON 35 EE-II COMPACT CAMERA

- | | |
|---|---|
| • Type: 35 mm Lens Shutter EE Compact Camera. | • Range Finder: Double image alignment type; closest focusing distance, 1 m (3.5 feet). |
| • Negative Size: 24 mm × 36 mm. | • Film Wind: Single stroke. |
| • Film: 35 mm Film. | • Film Counter: Automatically indicates number of exposures and resets to zero when the camera back is opened. |
| • Lens: F/2.7 38 mm, 4-elements in 3 groups. | • Film Rewind: Folding crank type. |
| • Viewfinder: Bright frame, Parallax compensation mark. Over/Under, Correct (battery check) Exposure warning signal visible. Magnification 0.5 X. | • Flash Provision: Hot shoe, X-sync at 1/30 sec. |
| • Shutter: Aperture priority electronic shutter, behind the lens type, Built-in self-timer at 8 sec., EV 1-17 (ASA100). Variable shutter speeds from 4 - 1/500 second. | • Function Lamp: The red function lamp will illuminate while the shutter operates. |
| • Exposure Meter: CdS automatic exposure system 1.4 V mercury battery × 2. ASA 25 - 800 (DIN 15 - 30). | • Dimensions: 113 (L) × 70 (H) × 53 (W) mm. (4.45" × 2.76" × 2.09") |
| | • Weight: 330 gr. (0.726 lbs.) |