

CHINON

35F-M

**COMPACT FULL FRAME 35MM CAMERA WITH BUILT-IN
MOTORIZED FILM TRANSPORT AND ELECTRONIC FLASH.**

FEATURES

- Motorized film transport automatically advances the film after each exposure.
- Built-in electronic flash.
- Piezo ceramic buzzer gives audible signal when the entire roll of film has been exposed.
- Battery check via red LED and piezo ceramic buzzer.
- Ultra sharp Chinon 38mm F/2.8 four element glass lens. Full color corrected coating.

- Programmed electronic shutter system with speeds from 1/60th to 1/350th.
- Film transport and electronic flash powered by two "AA" batteries.
- Variable film speeds range from 25 to 500 ASA.

ACCESSORIES

- | | |
|-------|-----------------------------|
| 28640 | Metal Table Tripod |
| 12505 | Replacement Lens Cap (43mm) |
| --- | Battery Pack |



APPROXIMATE SIZE

35mm COMPACT CAMERA

CHINON

35F-M

SPECIFICATIONS


- **Type:** 35mm EE Compact Camera with built-in flash and film power winder.
- **Negative Size:** 24 x 36mm.
- **Film:** 35mm film color prints, color slides or black and white prints.
- **Lens:** 38mm F/2.8, 4 glass elements in 3 groups.
- **Shutter:** Programmed EE shutter (EV 9-17: ASA100) Variable shutter speed from 1/60 to 1/350 sec., Daylight Flash sync. possible, Behind the lens type.
- **Viewfinder:** Bright Line Frame, Parallax Compensation Mark, F/Stop Indication Mark, Over and Under exposure Indicator, Flash ready light, Zone Focus Mark.
- **Exposure Meter:** Cds automatic exposure system, ASA 25-500 (DIN 15-28) 1.35V mercury battery source (H-C, PX-675 or equivalent).
- **Focusing:** Zone focusing system by utilizing the symbol mark with range of 1 meter to infinity (3.2 ft - ∞).
- **Flash Unit:** Built-in Electronic flash unit.
*Guide Number: 12 (ASA 100: M), 39 (ASA 100: Ft).
*Recycling Time: Approx. 7 sec. with alkaline batteries.
*Effective Flash Distance: 1-4.5 meter (ASA 100).
3.2-14.7 ft. (ASA 100).
*Number of Flashes: Approx. 250 with alkaline batteries.

- **Film Wind:** Built-in motor winder.
- **Film Counter:** Automatically indicates number of exposure and resets to "S" position when the camera back is opened.
- **Film End Signal:** Built-in — Blinking red LED and electronic sound (Piezo Ceramic Buzzer) during red LED operation.
- **Film Rewind:** Folding rapid crank type with film rewind indicator.
- **Battery Check:** Built-in red LED and electronic sound (PCB) for "AA" size batteries.
- **Shutter Release Lock:** Built-in.
- **Others:** Battery Pack Capability.
- **Power Source:** Two 1.5V "AA" size alkaline batteries for film winding and flash.
- **Dimensions:** 135 (W) x 79 (H) x 52 (D) mm, (5.31" x 3.11" x 2.05").
- **Weight:** 450 g. (15.8 oz.).

STANDARD PACKAGING

PRODUCT NUMBER	DESCRIPTION
39100	CHINON 35F-M
---	Case
---	Shoulder Strap with Pad
---	Lens Cap
---	Instruction Book

VIEWFINDER



1. Bright line frame
2. Parallax mark
3. Flash ready lamp
4. Over exposure warning zone
5. Correct exposure range
6. Exposure meter needle
7. Under exposure warning zone
8. Zone focusing symbols
9. Zone focus needle

