

CHINON

35FA II AUTO PROGRAM

COMPACT 35MM CAMERA WITH BUILT-IN AUTO FOCUS, AUTO LOAD,
AUTO WIND, AUTO REWIND AND ELECTRONIC FLASH

FEATURES

- Automatic infrared focusing system from 3.93 feet to infinity.
- Cancellable auto focus memory lock; allows subject to be positioned anywhere in the viewfinder.
- ASA 1000 setting.
- Bright viewfinder with low light warning indicator (red LED) and film transport signal indicator (green LED), battery check indicator (red LED).
- Automatic film advance.
- Automatic film rewind.
- Built-in electronic flash with a guide number of 40 at ASA 100:ft., (12 at ASA 100:M) and day light sync.
- Film transport indicator.
- Automatic film loading system.
- Electronic self timer with 2 speed flash LED.
- Seiko electronic programmed shutter with automatic low voltage lock system.
- Silicon photodiode automatic exposure system.
- Sliding cover fully protects lens from dust, moisture and foreign elements.
- Chinon four element glass 35mm f/3.5 color corrected lens.

ACCESSORIES

PRODUCT NUMBER	DESCRIPTION
28406	Metal table tripod
40215	Soft case



APPROXIMATE SIZE

35mm COMPACT CAMERA

CHINON

35FA II AUTO PROGRAM

SPECIFICATIONS

TYPE: 35 mm EE compact Infrared Auto-Focus camera with auto film load, auto wind, auto rewind and built-in flash system.

PICTURE FORMAT: 24 × 36 mm.

LENS: 35mm F3.5, 3 elements in 3 groups.

VIEWFINDER: Under exposure warning/battery check indicator, and film advance indicator.

SHUTTER: Programmed electronic shutter (EV 8.6 – 17: ASA100) with automatic lock system at low voltage.

EXPOSURE METER: SPD Automatic exposure system

ISO/ASA RANGE: 100, 200, 400 and 1000.

FOCUSING: Infrared automatic focusing system with possible prefocus and AF resuming; cancellable.

FOCUSING RANGE: 1.2 M (3.9 ft) to infinity.

FILM LOADING: Auto loading system by built-in motor.

FILM WIND: Automatic power winder for single frame advance and continuous exposure.

FILM REWIND: Automatic power rewinding when at end of roll of film.

AUTO REWIND STOP: Film rewinding automatically stops upon completion.

FILM COUNTER: Automatically indicates number of exposures and resets to "S" when camera back is opened.

SELF-TIMER: 10 sec. electronically controlled with 2 speed flashing LED.

FLASH UNIT: Built-in flash unit with possible daylight sync.

GUIDE NUMBER: 12 (ASA 100:M), 39 (ASA 100: Ft)

RECYCLING TIME: Approx. 6 sec with alkaline batteries.

EFFECTIVE FLASH DISTANCE: 1.2 – 3.4M (3.9 – 11.2 ft), ASA 100

OTHER FEATURES: Magnetic shutter release, film type window, shutter release lock activated by closing lens cover, Manual rewind switch, tripod mount screw.

POWER SOURCE: Two 1.5 V "AA" size alkaline batteries. (LR6)

DIMENSIONS: 133 × 69 × 47 mm (5.24" × 2.72" × 1.85")

WEIGHT: 315 grams (11.11 oz).

STANDARD PACKAGING

PRODUCT NUMBER	DESCRIPTION
39300	35FA II
— — —	Instruction book

