

CHINON

AUTO S-360

DEDICATED, DIGITAL, AUTOMATIC THYRISTOR DUAL ELECTRONIC FLASH
WITH SWIVEL HEAD FOR CHINON SERIES "4" AND "5" CAMERAS.

SPECIFICATIONS:

- **Type:** Thyristor Electronic Flash with information display by LED (Power cut-off system)
- **Auto Flash System:** Yes
- **Dedicated for Series "4" and "5" cameras:** Yes
- **Guide Number in M:** 36, Dual Flashes (ASA100/DIN21) 36, Main Flash (ASA100/DIN21) 12, Sub Flash (ASA100/DIN21)
- **Setting:** ASA50 F2/F4/F8, ASA100 F2.8/F5.6/F11, ASA400 F5.6/F11/F22
- **Manual Flash:** Yes
- **Automatic Operation, Illumination:**

F-stop selection	Covering Angle		
	35 m/m	Wide Filter 28 m/m	Tele Filter 85 m/m
Effective flash distance (M)			
2.8	1.5-13 m	1.3-11 m	2.0-15 m
5.6	1.0-6.5	0.7-5.5	1.5-7.5
11	0.7-3.3	0.5-2.8	1.0-4.0
Illumination Angle:			
	Vertically Horizontally	45° 60°	53° 70°

- **ASA/ISO Range:** 50/64, 100, 400 (DIN 18/19, 21,27)
- **Sensor Acceptance Angle:** Approx. 20°C
- **Flash Duration:** Automatic 1/30,000—1/500 sec., Manual 1/500 sec.
- **Recycling Time:** Auto: 0.5—10 sec.*, Manual: 10 sec.*
- **Number of Flashes:** 120*
- **Bounce System:** Vertically 90°, Horizontally 320°
- **Power Source:** Four AA size 1.5V batteries
- **Open Flash Button:** Yes
- **Sync. Jack:** Yes
- **Special Features:** Wide/Tele filters included, Digital Display shows F-stop and distance by LED
- **Accessories:** Power pack
- **Dimensions:** 86(W) × 142(H) × 85(D)mm
- **Weight:** 400 grams (14.1 oz)

(*With alkaline batteries)



35mm SLR ACCESSORY

CHINON