

**AUTO 2001 AUTO PROGRAM  
SENSOR FLASH**

**COMPACT 35 MM CAMERA WITH BUILT IN AUTO FOCUS, AUTO LOAD, AUTO WIND,  
AUTO REWIND, ELECTRONIC SENSOR FLASH AND DX AUTOMATIC FILM SPEED SETTING**



APPROXIMATE SIZE

**ACCESSORIES**

| PRODUCT<br>NUMBER | DESCRIPTION                  |
|-------------------|------------------------------|
| 40216             | Deluxe soft case             |
| 40211             | Standard soft case           |
| *****             | Auxiliary tele<br>angle lens |

**FEATURES**

- Automatic active infrared focusing system from 33" to infinity.
- Cancelable auto focus memory lock; allows subject to be positioned anywhere in the viewfinder.
- Automatic DX film speed setting: ISO 50-1600.
- Manual film speed setting for non-DX films: ISO 100, 200, 400, 1000.
- Full information viewfinder with: AF distance symbols and minimum focus warning (red LED), auto focus frame, film advance indicator (green LED), strobe indicator (red LED), parallax compensation mark.
- One-touch automatic film loading system.
- Automatic film advance.
- Continuous film advance provision.
- Automatic film rewind with auto stop.
- Built-in electronic sensor flash with a guide number of 25 at ASA 100: FT., (7.5 at ASA 100: M) and day light sync.
- Two second recycling time.
- Non-flash override provision.
- Electronic self-timer with flashing LED, cancelable.
- SEIKO electronic programmed shutter.
- CDS automatic exposure system.
- User replaceable lithium battery pack for extended life.
- Sliding cover fully protects lens and viewfinder from dust, moisture and foreign elements.
- CHINON four element glass 35 mm F/2.8 color lens.

**CHINON**

# AUTO 2001 AUTO PROGRAM SENSOR FLASH SPECIFICATIONS

**Type:** Lens shutter type fully automatic 35 mm compact camera with built-in sensor flash

**Film type:** 35 mm standard casset

**Picture size:** 24 × 36 mm

**Lens:** Newly designed 35 mm F2.8 lens constructed with 4 elements in 4 groups

**Finder:** Inversed galilean finder with AF frame parallax compensation mark and AF distance LED/minimum AF distance warning. Film advance indicator LED (green) and strobe indicator LED (red) are built into the viewfinder frame

**Focusing system:** Infrared AF system with possible prefocus, cancellable

**Shooting range:** 0.85 m (33.46") to infinity

**Shutter:** Programmed electronically controlled shutter with electromagnetic shutter release

**Shutter speed:** 1/45 sec (F2.8)–1/500 sec (F16)

**Selftimer:** 10 sec. electronically controlled with LED indication

**Exposure meter type:** Programmed EE with CdS photocell

**EV range:** EV8.5–EV17 (ISO 100)

**ISO range:** ISO 50 to 1600 for auto setting with DX film and ISO 100, 200, 400 & 1000 for manual setting (Non DX film)

**Film transport:** Automatic film loading with automatic first frame setting, automatic winding, automatic rewinding with autorewind start & stop system

**Frame counter:** Progressive type. Returns frame by frame along with the automatic film rewinding plus automatic reset with back cover opening

**Manual rewind:** Possible with manual rewind switch

**Flash:** Sensor flash type flashmatic with auto charging system

**Effective range:** 0.85 to 4.0 m (2.8 to 3.1 ft) at ISO 100–200, 0.85 to 8 m (2.8 to 26.2 ft) at ISO 400–1600 (with color negative film only)

**Recycling time:** 2 sec.

**Ready light:** Built-in LED indicates flash changing/flash ready/flash not ready & flash firing

**Flash override:** Daylight sync. and non flash mode can be selected by flash override switch

**Other features:** Built-in film type window, dust barrier, tripod screw and attachable hand/neck strap. Continuous shooting is possible in the non-flash mode and shutter release lock is coupled with the sliding lens cover.

**Power source:** 6V lithium battery pack (2/3A-2) (consumer replaceable)

**Battery life:** About 5 years if yearly 12 rolls of 24 exposure films are taken with 50% flash pictures.

**Size:** 133(W)×67(H)×43.5(H)mm

**Weight:** 275 g (9.7 oz) without lithium battery pack

## STANDARD PACKAGING

### PRODUCT NUMBER DESCRIPTION

|       |                  |
|-------|------------------|
| 39420 | Auto 2001        |
| ----- | Instruction book |

