# **AUTO-FOCUS LENS**

#### 35-70MM F/3.3-4.5

## **FEATURES:**

### Catalog # 33600

- Infrared Auto Focus.
   Stepless operation: 1M (3.3ft.) ∞, minimum focus distance 0.5M (on manual)
   Built-in AF indicators (red/green LED's)
   In Focus (green) LED
   Auto focus audible signal (piezo ceramic buzzer) with on/off
- control.

  Built-in electronic AF contacts permit activation of AF system from shutter release button of CHINON "Series 5" cameras.

  Shutter will not release unless lens is in focus (when used with CHINON CE-5 and CG-5 SLR cameras).

  Minimum aperture: f/22

  Battery check via LED.

- AF operation visible in viewfinder when used with CHINON SLR models CE-5 and CG-5
   Powered by three "AAA" alkaline batteries (LR03 or E92)



#### SPECIFICATIONS:

- System: Infrared automatic focusing system with manual focusing provision
- Auto Focus Indicator: Built-in with red and green LED



- Auto-focus Audible Signal with On/Off Control: Built-in (Piezo ceramic buzzer)
- Auto-Focus Button: Electronically operates Auto-Focus system
- Special Electronic Contacts to Camera Body: When the shutter release button is depressed, the lens is automatically set to the correct focusing distance.

#### Unless the lens is set, the shutter is not released. Auto-focus indicator (green LED) in the camera viewfinder

CHINON

- Focus Range: Stepless operation from 1.0M (3.3 ft.) to infinity on automatic focusing position, 0.5M (1.65 ft.) to infinity on manual focusing position
- Aperture Range: F/3.3-F/22
- Battery Check: Via green LED
- Battery: Three AAA size alkaline batteries (LR03 or E92) operate the auto-focus unit
- Power On/Off Switch: Built-in
- Lens: Chinon F/3.3-4.5 35-70mm multi-coated zoom lens
- Lens Construction: 7 elements in 7 groups
- Lens Mount: Chinon bayonet mount
- Filter Size: 52mm
- Dimensions: 101(W)  $\times$  83(H)  $\times$  88.5(L) (3.97"  $\times$  3.26"  $\times$  3.48")
- Weight: 630 grams (22.22 oz) without batteries

IN JUM MONIN



#### Catalog # 26210 **FEATURES:**

- Infrared Auto Focus
- Stepless operation: 1M (3.3 ft ) − ∞
   Built-in AF indicators (red/green LED's)
- In Focus (green) LEDAperture range: f/1.7 22
- Auto Focus audible signal (piezo ceramic buzzer) with on/off control
- Cancellable pre-focus lock
  Powered by 3 "AAA" alkaline batteries (LR03 or E92)
  Battery check via LED

  Output

  Description:
- AF operation visible in viewfinder when used with CHINON SLR models CE-4s, CE-5.

#### SPECIFICATIONS:

- System: Infrared Automatic Focusing System with Manual Focusing Provision.
- Auto Focus Indicator:



Visible green LED in the CE-4s/CE-5 viewfinder

- Auto Focus Audible Signal with On/Off Control: built-in (piezo ceramic buzzer)
- Auto Focus Button: Electronically operates AF system.
- Focus Range: Stepless operation from 1M (3.3 ft) to ∞.
- Aperture Range: F/1.7 F/22.
- Battery Check: Via green LED.
- Battery: 3 AAA size Alkaline batteries (LR03 or E92:  $1.5 \times 3$ ) operate the auto focus unit.
- Chinon F/1.7 50mm multi-coated lens.
- Lens Construction: 6 elements in 5 groups.
- Angle of View: 46°.
- Filter Size: 58mm
- Lens Mount: Chinon Bayonet Mount.
- Dimensions: 99(W) × 79(H) × 54(L)mm (3.89" × 3.11" × 2.12")
- Weight: 425 grams (14.99 oz) without batteries.

