

CHINON

CE-4 MEMOTRON™

**FULLY AUTOMATIC SLR WITH MANUAL EXPOSURE OVERRIDE
AND BAYONET MOUNT LENS.**

FEATURES

- Creative full manual override VIA a match LED system in the viewfinder.
- Information packed viewfinder employing 16 LED's indicating shutter speeds and over and under exposure situations.
- Brightness of viewfinder LED's vary automatically.
- Electronic metal Seiko shutter with automatic stepless speeds from 8 sec. to 1/1000.
- Employs two instant responding silicon blue cells. Center weighted full aperture metering system.

- Accepts lenses with universal bayonet mount and accepts thread mount lenses with optional adapter.
- Two dedicated CHINON electronic flashes which automatically set the proper flash synchronization shutter speed.
- Exposure memory lock for back light or spot light situations.
- Unlimited multiple exposures with perfect registration.
- Memo holder so that you always know what type of film is in your camera.
- Compact/lightweight design.
- Two stage electronic LED self-timer allows 5 or 10 second delay of shutter release, plus "flicker" feature.
- Depth of field preview system.
- Accepts CHINON power winders (PW-530, 540)
- Compatible with CHINON wireless remote control system.

ACCESSORIES

PRODUCT NUMBER	DESCRIPTION
27535	Deluxe case for CE-4
24905	Power winder (PW-530)
24910	Power winder (PW-540)
28940	Wireless remote control for power winders
28900	S-180 Auto electronic flash
28910	S-240 Dedicated automatic electronic flash
28920	S-280 Dedicated automatic electronic flash
28350	Right angle finder
28202	Eyeiece diopter -3.0
28212	Eyeiece diopter +1.0
28222	Eyeiece diopter +3.0
28815	Lens cap (49mm)
28880	Neck strap for CE-4, CA-4, CM-4, CS-4
28405	Extension tube set (12, 20, 36mm)
28415	Extension bellows
28560	Rubber eyepiece
6020	Lens hood (49mm)
28640	Metal table tripod



APPROXIMATE SIZE

35mm SLR CAMERA

CHINON

CE-4 MEMOTRON™

SPECIFICATIONS

- **Type:** 35mm automatic SLR (Single Lens Reflex) compact camera with aperture priority exposure system (AE).
- **Picture Format:** 24 x 36 mm.
- **Lens Mount:** Chinon universal bayonet mount. (Thread mount lenses can be used with optional adapter).
- **Mirror:** Large, Quick Return, shockless system.
- **Shutter:** Seiko MFC-846 electromagnetic metal focal plane shutter, stepless speeds from 8 to 1/1000 sec. on automatic; 13 speeds from 4 to 1/1000 sec. on manual; "B." Both automatic and manual speeds electronically controlled.
- **Shutter Release:** Two stage electromagnetic type with safety lock and provision for cable release.
- **Viewfinder:** Fixed eye-level pentaprism, central split image with microprism collar and ground glass, 16 LED's indicate shutter speeds and over/under exposure.
- **Viewfinder Magnification:** 0.87 x (@ 50mm, ∞).
- **Viewfinder Visibility:** 92%.
- **Depth of Field Preview:** By depressing depth of field lever.
- **Exposure Meter:** TTL, Center weighted full aperture system employing two silicon blue photo cells. Brightness of exposure LED's vary depending upon brightness of viewfinder.
- **Exposure Compensation:** Built-in ± 1 EV in one third stop increments.

- **Exposure Range:** EV-2 (F/1.4 8 sec.) to EV + 19 (F/22 1/1000) ASA 100 F/1.4 lens.
- **Memory Lock:** Built-in exposure memory lock system.
- **ASA Range:** 25-3200 (DIN 15-36) with safety lock.
- **Film Advance:** Single stroke in an arc of 130° with 25° stand off, provision for power winder.
- **Multiple Exposure:** Built-in switch which disengages film advance and frame counter.
- **Film Counter:** Automatically indicates number of exposures and resets to "S" when camera back is opened.
- **Self-Timer:** Electronically controlled at 5 or 10 seconds with flashing red LED indicator. Cancellable.
- **Film Rewind:** By depressing the rewind button and cranking the rewind lever.
- **Accessory Shoe:** Hot shoe type with X sync. and contact for Chinon dedicated flash.
- **Synchronization:** "X" strobe sync. at 1/60 sec.
- **Power Source:** Three 1.5V silver oxide G-13 batteries (S-76 type).
- **Battery Test:** Built-in with LED indicator.
- **Accessories:** Chinon Power Winders, Chinon dedicated flashes, Deluxe carrying case, Super Multi-coated lenses, and many more.
- **Body Dimensions:** 135.5 (W) x 85.0 (H) x 50.5 (D) mm (5.33" x 3.34" x 1.99")
- **Body Weight:** 485 grams (17.10 oz.)

STANDARD PACKAGING WITH F/1.7 MC LENS #22003


PRODUCT NUMBER DESCRIPTION

24850	CE-4 memotron body
26200	50mm f/1.7 MC lens
28115	Snap-in front lens cap (49mm)
28880	Shoulder strap with pad and "D" rings
----	Rear lens cap
----	Body cap
----	Three G-13/S-76 batteries
----	Instruction book

AVAILABLE AS FOLLOWS:

PRODUCT NUMBER DESCRIPTION

22011	CE-4 with f/1.9 lens
22003	CE-4 with f/1.7 MC lens
22007	CE-4 with f/1.4 MC lens
22001	CE-4 with 45mm f/2.8 lens
24850	CE-4 body only



VIEWFINDER

1. Split image rangefinder
2. Microprism collar
3. Ground glass
4. Over exposure LED
5. Under exposure LED
6. Shutter speed scale
7. Shutter speed LED

