

CHINON

CE-4s MEMOTRON™

**FULLY AUTOMATIC SLR WITH MANUAL EXPOSURE
OVERRIDE AND BAYONET MOUNT LENS.**

FEATURES

- Creative full manual override VIA a match LED system in the viewfinder.
- Information packed viewfinder employing 16 LED's indicating shutter speeds and over and under exposure situations. Aperture visible in viewfinder.
- Brightness of viewfinder LED's vary automatically.
- Electronic metal Seiko shutter with automatic stepless speeds from 4 sec. to 1/2000.
- Employs two instant responding silicon blue cells. Center weighted full aperture metering system.



- Accepts lenses with universal bayonet mount and accepts thread mount lenses with optional adapter.
- Two dedicated CHINON electronic flashes which automatically set the proper flash synchronization shutter speed.
- Exposure memory lock for back light or spot light situations.
- Unlimited multiple exposures with perfect registration.
- Memo holder so that you always know what type of film is in your camera.
- Compact/lightweight design.
- Two stage electronic LED self-timer allows 5 or 10 second delay of shutter release, plus "flicker" feature.
- Depth of field preview system.
- Accepts CHINON power winders (PW-530,540).
- Compatible with CHINON wireless remote control system.

ACCESSORIES

PRODUCT NUMBER	DESCRIPTION
27535	Deluxe case for CE-4
24905	Power winder (PW-530)
24910	Power winder (PW-540)
28940	Wireless remote control for power winders
28900	S-180 Auto electronic flash
28910	S-240 Dedicated automatic electronic flash
28920	S-280 Dedicated automatic electronic flash
28350	Right angle finder
28202	Eyepiece diopter -3.0
28212	Eyepiece diopter +1.0
28222	Eyepiece diopter +3.0
28815	Lens cap (49mm)
28880	Neck strap for "Series 4" SLR's
28405	Extension tube set (12,20,36mm)
28560	Rubber eyepiece
28640	Metal table tripod



35mm SLR CAMERA

CHINON

CE-4s MEMOTRON™

SPECIFICATIONS


- **Type:** 35mm automatic SLR (Single Lens Reflex) compact camera with aperture priority exposure system (AE).
- **Picture format:** 24 × 36mm.
- **Lens Mount:** Chinon universal bayonet mount. (Thread mount lenses can be used with optional adapter).
- **Mirror:** Large, Quick Return, shockless system.
- **Shutter:** Seiko MFC-E2 electromagnetic metal focal plane shutter, stepless speeds from 4 to 1/2000 sec. on automatic; 13 speeds from 2 to 1/2000 sec. on manual; "B". Both automatic and manual speeds electronically controlled.
- **Shutter Release:** Two stage electromagnetic type with safety lock and provision for cable release.
- **Viewfinder:** Fixed eye-level pentaprism, central split image with microprism collar and ground glass. 16 LED's indicate shutter speeds and over/under exposure. Aperture visible in viewfinder.
- **Viewfinder Magnification:** 0.87 × (@ 50mm, ∞).
- **Viewfinder Visibility:** 92%.
- **Depth of Field Preview:** By depressing depth of field lever.
- **Exposure Meter:** TTL, center weighted full aperture system employing two silicon blue photo cells. Brightness of exposure LED's vary depending upon brightness of viewfinder.
- **Exposure Compensation:** Built-in ± 1 EV in one third stop increments.
- **Exposure Range:** EV -1 (f/1.4, 4 sec.) to EV +20 (f/22, 1/2000) ASA 100 f/1.4 lens.
- **Memory lock:** Built-in exposure memory lock system.
- **ASA Range:** 25-3200 (DIN 15-36) with safety lock.
- **Film Advance:** Single stroke in an arc of 130° with 25° stand off, provision for power winder.
- **Multiple Exposure:** Built-in switch which disengages film advance and frame counter.
- **Film Counter:** Automatically indicates number of exposures and resets to "S" when camera back is opened.
- **Self-Timer:** Electronically controlled at 5 or 10 seconds with flashing red LED indicator. Cancellable.
- **Film Rewind:** By depressing the rewind button and cranking the rewind lever.
- **Accessory Shoe:** Hot shoe type with X sync. and contact for Chinon dedicated flash.
- **Synchronization:** "X" strobe sync. at 1/60 sec.
- **Power Source:** Three 1.5V (S-76 types, G 13, LR 44, A 76).
- **Battery Test:** Built-in with LED indicator.
- **Accessories:** Chinon Power Winders. Chinon dedicated flashes. Deluxe carrying case. Super Multi-coated lenses, and many more.
- **Body Dimensions:** 135.5 (W) × 85.5 (H) × 50.5 (D) mm (5.33" × 3.36" × 1.99").
- **Body Weight:** 500 grams (17.64 oz.)

STANDARD PACKAGING with f/1.7 MC Lens #22103

PRODUCT NUMBER	DESCRIPTION
24860	CE-4s Memotron body
26200	50mm f/1.7 MC lens
28115	Snap-in front lens cap (49mm)
28880	Shoulder strap with pad and "D" rings
----	Rear lens cap
----	Body cap
----	Three 1.5V batteries
----	Instruction book

AVAILABLE AS FOLLOWS:

PRODUCT NUMBER	DESCRIPTION
22111	CE-4s with f/1.9 lens
22103	CE-4s with f/1.7 MC lens
22107	CE-4s with f/1.4 MC lens
24101	CE-4s with 45mm f/2.8 lens
24860	CE-4s body only



VIEWFINDER

1. Split image rangefinder
2. Microprism collar
3. Ground glass
4. Over exposure LED
5. Under exposure LED
6. Shutter speed scale
7. Shutter speed LED
8. Aperture

