

CHINON

CE-5

FULLY AUTOMATIC APERTURE PRIORITY SLR WITH COMPLETE MANUAL EXPOSURE, PLUS BUILT-IN ELECTRONIC AUTO FOCUS AND AUTO DATE CONTACTS

FEATURES:

- Built-in AF electronic contacts.
- AF operation activated by CE-5 shutter release.
- Shutter will not "trip" until AF lens has completed focus.
- Creative full manual override VIA match LED system in the viewfinder.
- Full information viewfinder employing 18 multicolored LED's indicating shutter speed, over and under exposure situation, slow shutter speed warning, auto focus confirmation and flash ready confirmation. Aperture also visible in viewfinder.



- Electronic metal SEIKO shutter with automatic stepless speeds from 4 sec. to 1/2000.
- Detachable hand grip with spare battery compartment.
- Electronic visual and audible 10 sec/5 sec self-timer.
- Built-in auto date electronic contact for use with CHINON auto date accessory back.
- Employs two instant responding silicon blue cells, center weighted full aperture metering system.
- Accepts "K" mount lenses.
- Three dedicated CHINON electronic flashes which automatically set the proper flash synchronization shutter speed.
- Exposure memory lock for back light situations.
- Unlimited multiple exposures via built-in lever.
- Memo holder so that you always know what type of film is in your camera.
- Compact/lightweight design.
- Depth of field preview lever.
- Accepts CHINON power winders (PW-530, PW-540, PW-535, PW-545).
- Compatible with CHINON wireless remote control system.

* CHINON AUTO FOCUS Lenses with AF contacts

ACCESSORIES

PRODUCT NUMBER	DESCRIPTION
28940	Wireless remote control for power winders.
28900	S-180 auto electronic flash.
28910	S-240 dedicated automatic electronic flash.
28920	S-280 "bounce" dedicated automatic electronic flash.
28925	S-360 "bounce and swivel" dedicated automatic electronic flash with information display by LED.
28350	Right angle finder
28202	Eye piece diopter -3.0
28212	Eye piece diopter +1.0
28222	Eye piece diopter +3.0
28880	Neck strap for "Series 5" SLR's
28405	Extension tube set (12, 20, 36mm)
28415	Extension bellows
28560	Rubber eye piece
28640	Metal table tripod
28000	Info Back digital data imprinting unit.
28060	Info Back-2 digital data imprinting unit with LCD monitor window
28080	Auto date digital data imprinting unit
33600	CHINON 35 — 70 f/3.3 — 4.5 auto focus lens
26210	CHINON 50AF f/1.7 auto focus lens.
24905	Power Winder PW-535
24910	Power Winder PW-545
24905	Power Winder PW-530
24910	Power Winder PW-540



35mm SLR CAMERA

CHINON

CE-5

SPECIFICATIONS

- **Type:** 35mm automatic SLR compact camera with aperture priority exposure system (AE)
- **Picture Format:** 24 × 36mm
- **Lens Mount:** Chinon universal bayonet mount
- **Mirror:** Large, quick return, shockless system
- **Shutter:** Seiko electromagnetic metal focal plane shutter, stepless speeds from 4 to 1/2000 sec. on automatic; 13 speeds from 2 to 1/2000 sec. on manual; "B". Both automatic and manual speeds electronically controlled.
- **Shutter release:** Two stage electromagnetic type with safety lock and provision for cable release.
- **Viewfinder:** Fixed eye-level pentaprism, central split image with microprism collar and ground glass, 18 LED's indicate shutter speeds (green) and over/under exposure (red), slow shutter speed warning (yellow), Flash ready (red), auto-focus indicator (green), aperture visible in viewfinder.
- **Viewfinder Magnification:** 0.87 × (@ 50mm, ∞)
- **Viewfinder Visibility:** 92%
- **Depth of Field Preview:** By depressing depth of field lever
- **Exposure Meter:** TTL, center-weighted full aperture system employing two silicon blue photo cells
- **Exposure Compensation:** Built-in ± 1 EV in one third stop increments
- **Exposure Range:** EV -1 (f/1.4 4 sec.) to EV +20 (f/22, 1/2000 sec.) ASA 100 f/1.4 lens
- **Memory Lock:** Built-in exposure memory lock system
- **ASA Range:** 25—3200 (DIN 15—36) with safety lock

STANDARD PACKAGING WITH F/1.7 MC lens

PRODUCT NUMBER	DESCRIPTION
24870	CE-5 body
26200	50mm f/1.7 MC lens
28115	Snap-in front lens cap (49mm)
28880	Shoulder strap with pad and "D" rings
28950	Rear lens cap
28840	Body cap
28865	Two 1.5V batteries (LR44)
— — —	Instruction book

- **Film Advance:** Single stroke in an arc of 130° with 25° stand-off, motorized film advance with optional Chinon power winders
- **Multiple exposure:** Built-in switch which disengages film advance and frame counter
- **Film Counter:** Automatically indicates number of exposures and resets to "S" when the camera back is opened.
- **Self-Timer:** Electronically controlled at 5 or 10 seconds with flashing red LED indicator and audible signal, Cancellable
- **Film Rewind:** By depressing the rewind button and cranking the rewind lever
- **Accessory Shoe:** Hot shoe type with X sync. and contact for Chinon dedicated flash
- **Synchronization:** "X" flash sync. at 1/60 sec.
- **Special Contacts for Chinon Auto-Focus Lens:** Built in with auto-focus indicator in viewfinder (green LED), unless the lens is set to the correct focusing distance, the shutter is not activated.
- **Special Contact for Auto-Date:** Built-in
- **Power Source:** Two 1.5V batteries (IEC SR44 or LR44 type, S76, G13, A76)
- **Battery Check:** Built-in with LED indicator
- **Accessories:** Chinon power winders, dedicated flashes, Info-Back data-imprinting unit, Auto Date digital data-imprinting unit, Super multi-coated lenses, Auto-focus lenses and many more.
- **Dimensions:** 135.5(W) × 88(H) × 50.5(D)mm (5.33" × 3.46" × 1.99")
- **Weight:** 490g (17.28 oz.)

