

CHINON CE II MEMOTRON



DISC

SPECIFICATIONS OF CHINON CE II MEMOTRON

- **Type:** 35mm Single Lens Reflex Camera with automatic, electronically controlled exposure system
- **Picture size:** 24mm × 36mm
- **Film:** 35mm film
- **Lens mount:** Praktica-type, screw-in mount
- **Standard lens:** Auto F/1.7, F/1.4 or F/1.2 f=55mm
- **Viewfinder:** Pentaprism finder with fresnel lens and microprism
- **Viewfinder shutter:** Built in viewfinder shutter to prevent extraneous light from affecting the exposure reading
- **Magnification:** 0.88× with 55mm lens
- **Mirror:** Quick return system
- **Shutter:** Metal focal plane, vertical path, electromagnetically controlled
- **Shutter speeds:** Auto 2 secs. - 1/2000 sec. (stepless)
Manual B, 1 sec. - 1/2000 sec., and "X"
Mechanical shutter operation at "X" (1/90 sec.)
- **Exposure meter:** TTL center weighted average measuring system employing Silicon blue cell. Automatic exposure range of EV 0-19 with ASA100 (2 secs. at f/1.4 to 1/2000sec. at f/16)
- **ASA speed:** ASA 25 - 3200
- **Film wind:** Single action winding lever in an arc of 134° with 20° play
- **Film counter:** Automatically indicates number of exposures and resets to zero when the camera back is opened.
- **Self-timer:** 6 - 10 seconds
- **Exposure memory:** Push button with lock in conjunction with shutter release button
Indication by a green signal lamp
- **Film rewind:** Folding crank type
- **Accessory shoe:** Built in hot shoe
- **Synchronization:** FP and X. (X=1/90 sec.)
- **Multiple exposure:** Multiple exposure provision
- **Power source:** 6V silver oxide battery cell of 4G-13 type. (Eveready No. 544 or Mallory PX-28)
- **Battery test:** Indication by a green signal lamp
- **Dimension (Body only):** 145 (W) × 97 (H) × 54.5 (D) mm
- **Weight (Body only):** 760 gr.