



SPECIFICATION OF CHINON CM-3

- | | |
|--|--|
| * Type : 35 mm SLR (single lens reflex) compact camera with Seiko focal plane shutter and L.E.D. type light measuring system | * Film Wind : Single stroke in an arc of 135° with 20° stand off |
| * Picture Size : 24 x 36 mm | * Film Counter : Automatically indicates number of exposures and resets to zero when the camera is opened |
| * Film : 35 mm cartridge film | * Self Timer : 7-12 seconds |
| * Lens Mount : Pentax/Praktica M-42 Mount | * Film Rewind : Folding crank type |
| * Viewfinder Visibility : 95% of negative size | * Accessory Shoe : Built-in hot shoe |
| * Mirror : Quick return, shockless system | * Synchronization : "X" terminal (X = 1/100 sec.) |
| * Shutter : New Seiko MFC-M (metal focal plane shutter, vertical path) | * Power Source : Two silver oxide G-13 type batteries (Eveready S-76 or equivalent) |
| * Shutter Speeds : 1 sec. ~ 1/1000 sec., "B", "X" (X=1/100 sec.) | * Battery Test : Indication by green signal lamp (LED) in viewfinder frame - push button |
| * Exposure Meter : TTL, centre weighted measuring system employing two silicon blue cells, 5 step exposure indicator with 3 LEDs, Exposure range of EV1 ~ 18 at ASA 100 F/1.4 | * Accessory : Chinon Power Winder, Chinon Interchangeable lenses, various accessories |
| * ASA Range : 25-1600 (DIN 15-33) | * Dimensions : (Body only) 140.50 mm (w) x 88 mm (h) x 50 mm (d) (5.53" x 3.46" x 1.96") |
| | * Weight : (Body only) 610 g (21.51 oz.) |