

# CHINON

## CS-4

**SEMI-AUTOMATIC SLR ACCEPTING CHINON (M-42)  
THREAD MOUNT LENSES, MATCH LED EXPOSURE SYSTEM.**

### FEATURES

- Creative full manual control VIA match LED system.
- Seiko designed metal focal plane shutter with speeds from one second to 1/1000.
- Instant responding silicon blue cell employed in the center weighted metering system.
- Compact/lightweight design.
- Universal CHINON/Pentax (M-42) thread mount.
- Memo holder so that you always know what type of film is in your camera.

### ACCESSORIES

| PRODUCT<br>NUMBER | DESCRIPTION                                |       |                                       |
|-------------------|--------------------------------------------|-------|---------------------------------------|
|                   |                                            | 28202 | Eyepiece diopter -3.0                 |
|                   |                                            | 28212 | Eyepiece diopter +1.0                 |
| 27540             | Black custom case                          | 28222 | Eyepiece diopter +3.0                 |
| 28900             | S-180 Automatic electronic flash           | 28815 | Lens cap (49mm)                       |
| 28910             | S-240 Dedicated automatic electronic flash | 28880 | Neck strap for CE-4, CA-4, CM-4, CS-4 |
| 28920             | S-280 Dedicated automatic electronic flash | 28400 | Extension tube set                    |
|                   |                                            | 28410 | Extension bellows                     |
| 28350             | Right angle finder                         | 6020  | Lens hood (49mm)                      |
|                   |                                            | 28640 | Metal table tripod                    |



# CHINON

# CHINON

## CS-4

### SPECIFICATIONS

- **Type:** 35mm SLR Compact with LED type light measuring system.
- **Picture Format:** 24 x 36mm.
- **Lens Mount:** M-42 screw mount.
- **Mirror:** Quick return, shockless system.
- **Shutter:** Seiko MFC metal focal plane shutter, vertical path.
- **Shutter Speed:** 1 sec.-1/1000 sec., "B."
- **Viewfinder:** Fixed eye-level pentaprism, central split image with microprism collar and ground glass.
- **Viewfinder Magnification:** 0.87 x (@50mm, ).
- **Viewfinder Visibility:** 92%.
- **Exposure Meter:** TTL, center weighted measuring system employing a silicon blue cell, 3 step exposure indicator with 3 LEDs.
- **Exposure Range:** EV + 2 (F/1.9, 1 sec.) to EV + 18 (F/16, 1/1000 sec.)-ASA 100 F/1.9 lens.
- **ASA Range:** 25-1600 (DIN 15-33) with safety lock.
- **Film Advance:** Single stroke in an arc of 130° with 25° stand off.
- **Film Counter:** Automatically indicates number of exposures and resets to "S" when camera back is opened.
- **Film Rewind:** Folding crank type.
- **Accessory Shoe:** Hot shoe type with X sync.
- **Action Lamp:** Red LED illuminates while the shutter operates.
- **Synchronization:** Flash sync. at 1/60 sec.
- **Power Source:** Two 1.5V silver oxide G-13 batteries (S-76 type).
- **Battery Test:** Built-in LED indicator.
- **Accessories:** Multi-coated lenses, auto electronic flashes, carrying case and many more.
- **Body Dimensions:** 135 (W) x 86 (H) x 50.5 (D) mm. (5.33" x 3.38" x 1.99").
- **Body Weight:** 455 grams (16.05 oz.).


#### AVAILABLE AS FOLLOWS:

| PRODUCT NUMBER | DESCRIPTION                  |
|----------------|------------------------------|
| 18011          | CS-4 with 50mm f/1.9 lens    |
| 18003          | CS-4 with 50mm f/1.7 MC lens |
| 18007          | CS-4 with 50mm f/1.4 MC lens |
| 18001          | CS-4 with 45mm f/2.8 lens    |
| 24930          | CS-4 Body only               |

#### STANDARD PACKAGING WITH F/1.7MC LENS #18003

| PRODUCT NUMBER | DESCRIPTION                           |
|----------------|---------------------------------------|
| 24930          | CS-4 body                             |
| 26200          | 50mm f/1.7 MC lens                    |
| 28815          | Snap-in front lens cap (49mm)         |
| 28880          | Shoulder strap with pad and "D" rings |
| ---            | Rear lens cap                         |
| ---            | Body cap                              |
| ---            | Batteries                             |
| ---            | Instruction book                      |

#### VIEWFINDER



1. Over exposure Red LED
2. Correct exposure Green LED
3. Under exposure Red LED
4. Split image rangefinder
5. Microprism collar
6. Ground glass

Film speed window (ASA/DIN)

Film advance lever

Shutter speed dial

Frame counter

Shutter release button

Shoulder strap eyelet

Action lamp

Film rewind knob/ back cover opener

Hot shoe

Aperture ring

Depth of field scale

Exposure meter switch

Focusing ring

Viewfinder eyepiece

Exposure indicator LED's  
battery check lamp

Film chamber

Shutter

Film rail

Film guide rail

Battery compartment cover

Film chamber cover

Film pressure plate

Sprocket teeth

Take-up spool

Rewind button

Tripod socket

# CHINON