CHINON CS





SPECIFICATIONS OF CHINON CS

	• Type: 35mm Single Lens Reflex Camera with built-in	system employing CdS cell. Exposure measuring range of
	exposure control.	EV 3 – 18 with ASA 100.
	• Picture size: 24mm×36mm	• ASA Speed: ASA 10 - 1600 (DIN 11 - 33)
	• Film: 35mm film	Film Wind: Single stroke in an arc of 134° with 20° play.
	· Lens mount: Praktica-type, screw-in mount.	Film Counter: Automatically indicates number of exposures
	• Standard Lens: Auto F/1.7 or F/1.4 55mm.	and resets to zero when the camera back is opened.
	· Viewfinder: Pentaprism finder with fresnel lens and	• Film Rewind: Folding crank type.
	microprism.	Accessory Shoe: Built in hot shoe.
	• Magnification: 0.88× with 55mm lens.	 Synchronization: M and X. (X=1/125 sec.).
	• Mirror: Quick return system.	Power Source: 1.3 V mercury battery (Eveready No. EPX
/	Shutter: Metal focal plane, vertical path.	625 or Mallory No. PX625).
	• Shutter Speeds: B, 1 sec 1/1000 sec.	• Dimensions (Body only): $149 (W) \times 95 (H) \times 52 (D) mm$.
	• Exposure Meter: TTL center weighted average measuring	• Weight (Body only): 750 g. (1.65 lbs.)