

CHINON CX II

DISC



SPECIFICATIONS OF CHINON CX-II

- | | |
|--|---|
| • Type: 35mm Single Lens Reflex Camera with built-in exposure control. | into shutter release button. |
| • Picture size: 24mm x 36mm | • ASA Speed: ASA 10-1600 (DIN 11-33) |
| • Film: 35mm film | • Film Wind: Single stroke in an arc of 134° with 20° play. |
| • Lens mount: Praktica-type, screw-in mount. | • Film Counter: Automatically indicates number of exposures and resets to zero when the camera back is opened. |
| • Standard Lens: Auto F/1.7 or F/1.4 55mm. | • Film Rewind: Folding crank type. |
| • Viewfinder: Pentaprism finder with fresnel lens and microprism. | • Accessory Shoe: Built in hot shoe. |
| • Magnification: 0.88x with 55mm lens. | • Synchronization: M and X. (X=1/125 sec.). |
| • Mirror: Quick return system. | • Multiple Exposure: Multiple exposure provision. |
| • Shutter: Metal focal plane, vertical path. | • Power Source: 1.3 V mercury battery (Eveready No. EPX 625 or Mallory No. PX625). |
| • Shutter Speeds: B, 1 sec. - 1/1000 sec. | • Battery Test: Indication by a green signal lamp. |
| • Exposure Meter: TTL center weighted average measuring system employing CdS cell. Exposure measuring range of EV 3-18 with ASA 100. Exposure Meter Switch incorporated | • Dimensions (Body only): 149 (W) x 95 (H) x 52 (D) mm. |
| | • Weight (Body only): 750 g. (1.65 lbs.). |