

CHINON

POWER WINDERS 530/540

COMPACT POWER WINDER ACCESSORIES
FOR CHINON CE-4 MEMOTRON CAMERA

FEATURES: PW 530 Catalog #24905
PW 540 Catalog #24910

- Transports film up to 2 FPS
- Built-in Pre-select Frame Control Dial (4-24 exposures)*
- Built-in Interval Timer Dial (1-30 sec.)*
- Single/continuous mode dial
- Convenient contoured handgrip with shutter release
- Wireless Radio Remote Control provision
- Film transport LED
- Power indicator LED
- Operated by 4 "AA" batteries
- Tripod Socket



ACCESSORIES:

PRODUCT NUMBER	DESCRIPTION
28940	Wireless Remote Control System
6820	Remote Control Cable (15')
28640	Metal Table Tripod



CE-4 with PW 530 and
Wireless Remote Control System

SPECIFICATIONS:

PW 530/PW 540

- **Winding Speed:** Approx. 1/2 sec.
- **Shutter Speed Range:** Single: 8-1/1000 sec., Continuous: 8 - 1/1000 sec.
- **C/S Dial:** Power control switch - OFF; Single Frame - S; Continuous - C
- **Pre-Set Counter:** 0,4,8,12,16,20, and 24 frames*
- **Interval Timer:** 0,1,2,4,8,15, and 30 sec.*
- **Power Source:** 6V 4 AA (Penlite) Alkaline Batteries (By one touch detachable battery container)
- **Indication Lamp:** Red Indicator Lamp for "S" and "C"
- **Battery Life:** Minimum 20 cartridges 36 Exposure at Room Temperature
- **Shutter Release:** Activated with Camera Shutter Release Button or Winder Shutter Release Button
- **Remote Control:** 2.5mm Mini-Jack, Remote-Control Accessory Switch is available, Wireless Remote
- **Attachment:** Screw-in to the tripod socket with guide pin channel
- **Other:** Action Lamp (red LED), Computerized Auto-Stop device when the film is finished
- **Size:** 136.0 (L)×88.5 (H)×76.0 (W)mm (5.35"×3.48"×3.0")
- **Weight:** 230 g. (8.11 oz.)

*Model PW 530 only.

Wireless Remote Control System

WIRELESS TRANSMITTER (RC-510)

- **Output Power:** Less than 1mv.
- **Frequency:** 27.045 MHz
- **Modulation:** AM
- **Oscillator:** Crystal control
- **Occupied Band Width:** Less than ±10 KHz
- **Suprious & Harmonic:** Less than 4×10^{-9} W
- **Temperature Stability:** Within ±0.01% (-20°+60°)
- **Voltage Stability:** Within ±0.01% (voltage 80-120%)
- **Antenna:** 50cm Wire-antenna
- **Constant Distance:** Approx. 40 meters (130 ft.)
- **Battery:** One "AA" size battery
- **Battery Life:** Approx. 10 hours
- **Size:** 28 (D)×148 (L)mm (1.1"×5.82")
- **Weight:** Approx. 110 g. (3.53 oz.)

WIRELESS RECEIVER (RC-550)

- **Frequency:** 27.045 MHz
- **Receiver-System:** Single Superheterodyne
- **IF:** 455 KHz
- **Sensitivity:** 25 dB
- **Band-Width:** Less than 15 KHz (-60 dB)
- **Remote Control:** Possible with "ON/OFF Switch"
- **Battery:** One MN 1604 9V Transistor radio type
- **Size:** 110 (H)×65 (W)×24 (L)mm (4.2"×2.5"×0.94")
- **Weight:** Approx. 125 g. (4.48 oz.)